DL-6M Floor-standing High -Capacity Refrigerated Centrifuge



Technical Performance

- The max capacity of swing rotor is 6X1200ml
- It has micro-computer control , electronic lock and AC variable-conversion motor which delivers high torque
- LCD touch screen make visualized operation conveniently. (L600R)
- Imported compressor unit with Non-CFC refrigerant R404a
- Automatic rotor recognition make safety for multiple rotors choice. (L600R)
- Up to 100 user programs storage meet more demands . (L600R)
- It has self-locking , over-speed detection , over-temperature detection , imbalance detection that is automatic alarm device
- It has 9 levels acceleration and 10 levels deceleration to be setting according to the different requirement. Slow down freely is available. (L600R)
- 9 levels acceleration and deceleration. (DL-6M)
- Silastic sealed ring comfort to GMP, US FDA certificated

Specification

Model	DL- 6M
Max Speed	6000r min
Max RCF	6680X
Max Capacity	6x1200m
Speed Accuracy	10r min
Time Setting	S ~99h59 min59s
Temperature Setting	-20°C ~ +40°C
Temperature Accuracy	±1°C
Compressor Unit	French Tecumseh Compressor Unit R404a
Noise	＜65dB (A)
Power Supply	AC220V 50Hz 30A
Consumption	5kw

Rotor

Picture		Capacity	Max Speed	Max RCF	Adaptor			
No.1		6x500ml	6000r min	6680xg	50ml /100m/250ml			
No.2		6x1200ml	4200r min	5100xg	 1200ml Round Bucket	 6X19X1 0m1 Internal Thread	 6X15X15m1	 6x13x20ml
					 1200ml PP Bottle	 6X5X50m	 6X3X100m	 6x250ml
					 1200ml Oval Bucket			
					 316L SS Bucket	 6x300ml	 6x500m1	 6x1 000ml