Horizontal Cylindrical Pressure Steam Sterilizer





WS-150/200/280/400/500YDA

Technical Data

Model / Technical Data	LS-35LD	LS-50LD	LS-75LD	LS-100LD	LS-120LD
Sterilizing Chamber Volume	150L φ440×1000mm	200L φ515×1000mm	280L φ600×1000mm	400L Φ700×1100mm	500L Φ700×1300mm
Working Pressure	0.22MPa				
Working Temperature	134℃				
Adjustment of Temperature	105℃ - 134℃				
Time of Sterilization	0-60 min				
Time of Drying	0-60 min				
Heat Average	≤±2℃				
Power	9KW/380V 50Hz	9KW/380V 50Hz	12KW/380V 50Hz	18KW/380V 50Hz	18KW/380V 50Hz
Dimension	1400×600×1300	1400×670×1650	1400×770×1780	1430×880×1830	1800×900×1820
Transport Dimension	1550×750×1850	1560×820×1850	1680×920×2100	1600×1050×2100	1850×1050×2100
G.W/N.W	320/240 KG	350/260 KG	465/365 KG	530/420 KG	580/470 KG

Characteristics

- Sterilizing course automatic sterilization controlled,easy to operate
- With drying function,suitable dressing drying
- With over-temperature,over-pressure auto-protect device
- The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the door doesn't close well
- The safety value will be open automatically when the inner pressure over 0.24MPa,and the steam be exhausting to the water tank
- The power will be cut-off automatically,cut-off the water and alarm when the machine lacking water
- The chamber of the sterilizer is made of stainless steel