Horizontal Cylindrical Pressure Steam Sterilizer



WS-150/200/280YDB

Technical Data

Model / Technical Data	WS-150YDB	WS-200YDB	WS-280YDB
Sterilizing Chamber Volume	150L φ440×1000mm	200L φ515×1000mm	280L φ600×1000mm
Working Pressure	0.22 MPa		
Working Temperature	134°C		
Adjustment of Temperature	40°C - 134°C		
Time of Sterilization	0-99 min		
Time of Drying	0-99 min		
Heat Average	≤± 2°C		
Power	9KW/380V 50Hz	9KW/380V 50Hz	12KW/380V 50Hz
Dimension	1400×650×1600	1400×750×1700	1520×910×1900
Transport Dimension	1560×820×1820	1560×910×1880	1680×1080×2100
G.W/N.W	430/340 KG	436/350 KG	570/462 KG

Characteristics

- Sterilizing course automatic sterilization controlled by computer, easy to operate
- With drying function, suitable dressing drying
- With over-temperature, over-pressure auto-protect device
- .The door opening mechanism cannot be operated until the pressure in the chamber is reduced to 0.027MPa.It can't be start on if the doesn't closed well
- The safety value will be open automatically when the inner pressure over 0.24MPa, and the steam be exhausting to the water tank
- The power will be cut-off automatically, cut-off the water and alarm when the machine lacking water
- The chamber of the sterilizer is made of stainless steel
- With printer