Stainless Steel Series Electric Blast Drying Oven

Product Application

This series oven is a batch-type drying oven used in universities, scientific research institutes, enterprises R&D centers, quality inspection and processing industry for baking, drying, heat treatment and constant temperature heating experiments of various objects in vacuum or protective atmospheres.



Stainless Steel Electric Vacuum Drying Oven



Stainless Steel Electric Blast Drying Oven

Product Features

- The non-deforming working chamber is made of high-quality type 304 stainless steel plate with clean surface and vacuum degree achieving 1 Torr.
  Mica heating plate is used as heating element. Its reasonable arrangement is beneficial for power saving
- Elegant appearance. The outer housing is made of stainless steel embossed plate.Unique structure design, without solder joints nor welding marks on the surface, making it more durable
- Advanced air heat insulation technology combined with high-quality thermal insulation material, making the oven surface temperature increase less than 60℃
- The door adopts high-quality tempered glass, high-temperature resistant and not easily broken
- Electric air inlet and outlet valves, safe and reliable
- Locking function. Heating can only proceed when the equipment is turned on. On the contrary, heating will stop when the equipment is turned off to avoid heat damage to the oven

Specifications

Product Name	Model	Working Chamber Dimensions (D*W*H)(mm)	Exterior Dimensions (D*W*H)(mm)	Rated Power (KW)	Rated Voltage (V)	Temperature Accurary (℃)	Note
Stainless Steel Electric Vacuum Drying Oven	ZHZ-B203	300*300*270	525*540*660	1.5	220	±0.1	Temperature range: RT+10-200℃, Temperatrue fluctuation: ≤±1℃ Temperature uniformity: ≤±2.5℃
	ZHZ-B503	340*415*370	570*665*800	2.5			
	ZHZ-B903	450*450*450	670*690*975	3.5			
Stainless Steel Electric Blast Drying Oven	ZHD-B703	360*380*450mm	690*540*777	1.7			Temperature range: RT+10-250℃, Temperatrue fluctuation: ≤±0.5℃ Temperature uniformity: ≤±1℃
	ZHD-B1403	460*480*550mm	790*640*877	2.7			
	ZHD-B2303	511*611*751mm	878*780*1137	5			