TD4 Tabletop Low -Speed Centrifuge



Technical Performance

- It has micro-computer control , electronic lock and DC brushless motor which is low noise and high speed accuracy
- Digital LCD screen make visualized operation conveniently
- Up to 9 user programs storage meet more demands
- It has self-locking , over-speed detection , over-temperature detection , imbalance detection that is automatic alarm device
- It has 9 levels acceleration and 10 levels deceleration to be setting according to the different requirement. Slow down freely is available
- Silastic sealed ring comfort to GMP, US FDA certificated

Specification

Model	TD4
Max Speed	4000r min
Max RCF	2500xg
Max Capacity	6x50ml
Speed Accuracy	±30r min
Time Setting	1s-99min59s/1min-99min
Noise	＜60 (dB A)
Power Supply	AC110V/AC220V, 50Hz-60Hz
Consumption	150w
Dimension (L×W× H)	330mmx420mmx280mm
Packing Size (L×W× H)	430mmx520mmx390mm
Net Weight (No rotor)	14kg

Rotor

Picture		Capacity	Max Speed	Max RCF	Adaptor
No.1		12x7ml	4000r/min	2220xg	/
No.1		18x7ml	4000r/min	2220xg	/
No.1		24x7ml	4000r/min	2220xg	/
No.1		12x10m/15ml	4000r/min	2220xg	1.5ml/5ml/7ml
No.1		18/24x10ml	4000r/min	2220xg	1.5ml /5m/7ml
No.1		12x20ml	4000r/min	2220xg	5ml/10ml
No.1		6x50ml	4000r/min	2220xg	15ml/20ml
No.1		8x15ml	4000r/min	2220xg	/
No.2		8x15ml	4000r/min	2220xg	/
No.3		8x15ml	4000r/min	2500xg	/