TG16.5 Tabletop High -Speed Centrifuge



Technical Performance

- It has micro-computer control , electronic lock and DC brushless motor which is low noise and high speed accuracy
- Digital LCD screen make visualized operation conveniently
- Up to 9 user programs storage meet more demands
- It has self-locking , over-speed detection, over-temperature detection, imbalance detection that is automatic alarm device
- It has 9 levels acceleration and 10 levels deceleration to be setting according to the different requirement. Slow down freely is available
- Silastic sealed ring comfort to GMP, US FDA certificated

Specification

Model	TG16.5
Max Speed	16500r/min
Max RCF	23669xg
Max Capacity	4x100ml
Speed Accuracy	±30r/min
Time Setting	1s-99min59s
Noise	<65dB(A)
Power Supply	AC110V/AC220V, 50Hz-60Hz
Consumption	750W
Dimension (L×W×H)	330mmx420mmx280mm
Packing Size (L×W×H)	430mmx520mmx390mm
Net Weight (No rotor)	20kg

Rotor

Picture		Capacity	Max Speed	Max RCF	Adaptor
No.1		12x5ml/2.2ml	16500r/min	18930xg	0.2ml/0.5ml
No.2		10x5ml	13000r/min	11400xg	0.5ml/1.5ml
No.2		12x5ml	13000r/min	11400xg	0.5ml/1.5ml
No.3		12x10ml	12000r/min	14800xg	1.5ml/5ml
No.3		8x15ml	12000r/min	14800xg	1.5ml/5ml
No.4		6x50ml	11000r/min	13000xg	15ml/20ml
No.5		4 x100ml	10000r/min	11570xg	10ml/20ml
No.11		4x10ml	6000r/min	3200xg	/
No.6		2x48ml	3000r/min	1400xg	/
No.7		24 x1.5ml	13200/min	16110xg	0.2ml/0.5ml
No.8		36 x0.5ml	16000r/min	23669xg	/
No.8		48 x0.5ml	16000r/min	23669xg	/
No.9		3x8ml/0.2ml	15000r/min	13800xg	/
No.10		48x1.5ml	12000r/min	15696xg	0.2ml/0.5ml