Vacuum Oven

Microprocessor Controller (With Timing Function)



Vacuum oven is designed especially for drying of material which is thermo-sensitive or decompounds and oxidative easily. It can be filled with inert gases, which is especially for a rapid drying of some compound material

Features

- Microprocessor controller
- Dual layer tempered glass door for clear observation
- Minimum heating time 50% less than traditional vacuum oven
- Interior chamber made from stainless steel with a mirror polished finish making for easy cleaning
- Standard with vacuum pump
- Direct heating and control by shelves: Each shelf has a separate temperature sensor, can be independently displayed and controlled temperature in setting, monitoring and timing, more accurate and stable(except model DZF-6216A & DZF-6094A)

Options

- LED lamp
- Inert gas valve
- Oil mist filter
- Intelligent programmable temperature controller (LCD)

Specifications

Model	DZF-6500	DZF-6930
Electrical Requirements (V/HZ)	AC380/50	AC380/50
Controller	LED display	
Power Consumption (W)	3800	5800
Temperature Range (°C)	RT+10~200	
Display Resolution (°C)	0.1	
Temperature Stability (°C)	±1	
Vacuum Degree (Pa)	133	
Ambient Temperature (°C)	+5~40	
Chamber Volume (L)	431	913
Internal Dimension (W*D*H)(mm)	630*810*845	750*1160*1050
External Dimension (W*D*H)(mm)	1000*1040*1855	1400*1395*2010
Shelves (pcs)	4 (Independent temp. control)	5 (Independent temp. control)
Chamber Materia	304 Stainless steel	