Vacuum Oven

LED Microprocessor Controller (With Timing Function)

Vacuum oven is designed especially for drying material which is thermosensitive , oxidative, decomposable easily. It can also work with inert gas to dry some compound material



Features

- 304 stainless steel, mirror polishing processing, easy to clean and maintain
- PID controller with over temperature alarm and timing function ensures precise and reliable control, also save more than 40% heating time
- A big dual layer tempered glass on the door provides good observation
- Door adjustment system with silicon door gasket ensures better vacuity

Options

- KF25 Vacuum Port
- LED lights on the door
- Inert gas valve

Specifications

Model	DZF-6022	DZF-6050	DZF-6032
Electrical Requirements (V/HZ)	AC220/50		
Controller	Controller LED display		
Power Consumption (W)	700	1450	850
Temperature Range (°C)	RT-10~200		
Display Resolution (°C)	0.1		
Temperature Stability (°C)	±1		
Vacuum Degree (Pa)	133		
Chamber Volume (L)	24	50	30
Ambient Temperature (°C)	+5~40		
Internal Dimension (W*D*H)(mm)	300*300*275	415*370*345	320*320*300
External Dimension (W*D*H)(mm)	605*490*450	730*560*550	630*510*490
Shelves (pcs)	2	2	2
Chamber Materia	304 Stainless steel		316 SS