Vertical Steam Sterilizer



Digital Displayed Automatic Type

Main Technical Parameter

Model	DGL-35B	DGL-50B	DGL-75B	DGL-100B
Volume	35L	50L	75L	100L
Power	3.5kw	3.5kw	4.5kw	4.5kw
Voltage	AC 220V/50HZ			
Design Pressure	0.25MPa			
Design Temperature	139℃			
Rated Working Pressure	0.22MPa			
Rated Working Temperature	134℃			
Steriization Temperature Seting Range	116℃ ~ 134℃			
Sterilization Time Setting Range	4 ~ 120 min			
Chamber Volume	Φ350x400	Φ350x525	Φ400x625	Φ450x650
Bucket Dimension	Φ330x320	Φ330x460	Φ380x560	Φ420x540
Basket Dimension	Φ320x350	Φ320x240x2	Φ360x280x2	Φ410x300x2
Outer Dimension	480x480x1000	480x480x1120	525x525x1190	555x555x1250
Packing Size (LxWxH)	580x630x1130	580x630x1230	630x680x1290	690x650x1410
Gross/Net Weight	92176kg	99/80kg	108/90kg	131/110kg

Features

- Hand wheel translation and quick opening structure
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Digital display and Touch buttons
- Self-expanding seal
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- High quality stainless steel material
- Safety interlocking device
- Standard test interface
- With automatic protection function: over temperature protection; over pressure self discharge protection; low water level protection; anti dry burning
- Automatic discharge of cold air, automatic steam exhaust after sterilization

*Optional automatic water