Vertical Steam Sterilizer



Multifuctional Automatic With Drying

Main Technical Parameter

Model	DGL-35G	DGL-50G	DGL-75G	DGL-100G
Volume	35L	50L	75L	100L
Power	3.5kw	3.5kw	4.5kw	4.5kw
Voltage	AC 220V/50HZ			
Design Pressure	0.25MPa			
Design Temperature	139℃			
Rated Working Pressure	0.22MPa			
Rated Working Temperature	134℃			
Steriization Temperature Seting Range	116℃ ~ 134℃			
Sterilization Time Setting Range	4 ~ 120 min			
Drying Time Setting Range	0 ~ 240 min			
Chamber Volume	Φ350x400	Φ350x525	Φ400x625	Φ450x650
Bucket Dimension	Φ330x320	Φ330x460	Φ380x560	Φ420x540
Basket Dimension	Φ320x350	Φ320x240x2	Φ360x280x2	Φ410x300x2
Outer Dimension	480x480x1000	480x480x1120	525x525x1190	550x550x1250
Packing Size (LxWxH)	580x630x1130	580x630x1230	630x680x1290	690x650x1410
Gross/Net Weight	94/78kg	101/82kg	110/92kg	134/113kg

Features

- Hand wheel translation and quick opening structure
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Digital display and Touch buttons
- With automatic protection function: over temperature protection; over pressure protection; low water level protection; anti dry burning
- Automatic discharge of cold air, automatic steam exhaust after sterilization
- High quality stainless steel material
- Safety interlocking device
- Self-expanding seal
- Standard test interface
- With drying function
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop

*Optional external printer
*Optional automatic water