Vertical Steam Sterilizer



Touch Screen Display (3-Times pre-vacuum)

Main Technical Parameter

Model	DGL-35M	DGL-50M	DGL-75M	DGL-100M
Volume	35L	50L	75L	100L
Power	3.5kw	3.5kw	4.5kw	4.5kw
Voltage	AC 220V/50HZ			
Design Pressure	0.25MPa			
Design Temperature	139℃			
Rated Working Pressure	0.22MPa			
Rated Working Temperature	134℃			
Steriization Temperature Seting Range	116℃ ~ 134℃			
Sterilization Time Setting Range	4 ~ 120 min			
Drying Time Setting Range	0 ~ 240 min			
Chamber Volume	Φ350x400	Φ400x505	Φ400x655	Φ450x650
Bucket Dimension	Φ330x320	Φ380x430	Φ380x560	Φ420x540
Basket Dimension	Φ320x350	Φ360x280x1	Φ360x280x2	Φ410x300x2
Outer Dimension	698x498x940	630x500x1180	725x525x1170	760x560x1260
Packing Size (LxWxH)	790x610x1130	800x600x1230	840x610x1310	870x650x1380
Gross/Net Weight	125/110kg	136/116kg	141/121kg	180/146kg

Features

- Hand wheel translation and quick opening structure
- Three times pre-vacuum
- Safety interlocking device
- Standard test interface
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Automatic water
- With automatic protection function: over temperature protection; over pressure self discharge protection; low water level protection; anti dry burning
- High quality stainless steel material
- LED touch screen display
- Self-expanding seal
- With drying function
- Automatic discharge of cold air, automatic steam exhaust after sterilization
- External steam Generator
- Buzzer reminder after sterilization, automatic stop
- Internal printer