Vertical Steam Sterilizer



Multifunctional Automatic Internal Cycle With Drying

Main Technical Parameter

Model	DGL-35X	DGL-50X	DGL-75X	DGL-100X
Volume	35L	50L	75L	100L
Power	3.5kw	3.5kw	4.5kw	4.5kw
Voltage	AC 220V/50HZ			
Design Pressure	0.25MPa			
Design Temperature	139°C			
Rated Working Pressure	0.22MPa			
Rated Working Temperature	134°C			
Steriization Temperature Seting Range	116°C ~ 134°C			
Sterilization Time Setting Range	4 ~ 120 min			
Drying Time Setting Range	0 ~ 240 min			
Chamber Volume	Φ350x400	Φ350x525	Φ400x625	Φ450x650
Bucket Dimension	Φ330x320	Φ330x460	Φ380x560	Φ420x540
Basket Dimension	Φ320x350	Φ320x240x2	Φ360x280x2	Φ410x300x2
Outer Dimension	698x498x940	630x500x1180	725x525x1170	788x588x1255
Packing Size (LxWxH)	790x610x1130	800x600x1230	840x610x1310	870x650x1380
Gross/Net Weight	116/96kg	121/101kg	134/113kg	140/122kg

Features

- Hand wheel translation and quick opening structure
- With drying function
- Safety interlocking device
- Standard test interface
- Self-expanding seal
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Digital display and Touch buttons
- With automatic protection function: over temperature protection; over pressure self discharge protection; low water level protection; anti dry burning
- Automatic discharge of cold air, automatic steam exhaust after sterilization, Internal steam cycle

*Optional external printer
*Optional automatic water