Vertical Steam Sterilizer



Bolt Digital Displayed Automatic Type

Main Technical Parameter

Model	DGLS-35B	DGLS-50B	DGLS-75B	DGLS-100B	DGLS-120B	DGLS-150B
Volume	35L	50L	75L	100L	120L	150L
Power	2.5kw	3.5kw	4.5kw	4.5kw	4.5kw	6.0kw
Voltage	AC 220V/50HZ					
Design Pressure	0.25MPa					
Design Temperature	139°C					
Rated Working Pressure	0.22MPa					
Rated Working Temperature	134°C					
Steriization Temperature Seting Range	116°C ~ 134°C					
Sterilization Time Setting Range	4 ~ 120 min					
Chamber Volume	Φ350x400	Φ350x525	Φ400x625	Φ450x650	Φ450x760	Φ500x780
Bucket Dimension	Φ330x320	Φ330x460	Φ380x560	Φ420x540	Φ420x660	Φ470x720
Basket Dimension	/	Φ320x240x2	Φ360x280x2	Φ410x300x2	Φ410x350x2	Φ460x350x2
Outer Dimension	400x400x860	480x480x960	525x525x1060	555x555x1080	555x599x1200	605x649x1210
Packing Size (LxWxH)	550x500x1030	580x630x1100	630x680x1190	690x650x1230	690x650x1330	750x700x1370
Gross/Net Weight	49/36kg	70/55kg	82/66kg	94176kg	96/77kg	111/90kg

Features

- Bolt structure
- Microcomputer automatic control, arbitrary set of sterilization parameters
- Standard test interface
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- High quality stainless steel material
- Digital display and touch buttons
- The container with automatic protection function: over temperature protection; over pressure protection self discharge; low water level protection, anti dry burning
- Automatic cooling air, sterilization end automatic exhaust steam